

## Catálogo de Productos

### Elefante® Clase 19x7

- Alma de Acero
- Negro
- Resistente a la Rotación
- 19x7



Tabla de Resistencias a la tension y Pesos (pulgadas)

Diámetro (pulgadas)	Peso Aproximado (lb/ft)	Resistencia a la Ruptura (lbs.)	
		Arado Mejorado	Arado Extramejorado
1/2	0.45	19,700	21,600
9/16	0.58	24,800	27,200
5/8	0.71	30,600	33,600
3/4	1.02	43,600	48,000
7/8	1.39	59,000	65,000
1	1.82	76,600	84,400
1 1/8	2.30	96,400	106,200
1 1/4	2.84	118,400	130,200
1 3/8	3.43	142,600	156,800
1 1/2	4.09	168,800	185,600

Normas de Referencia: ASTM-A-1-23; API 9A

Tabla de Resistencias a la tension y Pesos (milímetros)

Diámetro (mm)	Peso Aproximado (kg/m)	Resistencia a la Ruptura (Toneladas Metricas)	
		Arado Mejorado	Arado Extramejorado
13	0.67	8.9	9.8
14.5	0.86	11.2	12.3
16	1.06	13.9	15.2
19	1.52	19.8	21.8
22	2.07	26.8	29.5
26	2.71	34.7	38.3
29	3.42	43.7	48.2
32	4.23	53.7	59.1
35	5.10	64.7	71.1
38	6.07	76.6	84.2

Normas de Referencia: ASTM-A-1-23; API 9A

---